

Congratulations to your new TheBone-guitar®.

By TRIFF of Switzerland

Modelle: B 300-Stage

Here a few important and helpful tips, just enough to get you started and on your way.

8- way pick-up selection

3way-switch position

	<i>push/push A (closer fretboard)</i>	<i>push/push B (closer bridge)</i>	
1. Position A (fretboard)	IN Single-Coil (neck-PU)	no	
2. Position A (fretboard)	OUT Hummbucker (neck-PU)	no	
3. Position B (middle)	IN Single-Coil (neck-PU)	IN Single-Coil (bridge-PU)	
4. Position B (middle)	OUT Hummbucker (neck-PU)	IN Single-Coil (bridge-PU)	
5. Position B (middle)	IN Single-Coil (neck-PU)	OUT Hummbucker (bridge-PU)	
6. Position B (middle)	OUT Hummbucker (neck-PU)	OUT Hummbucker (bridge-PU)	
7. Position C (bridge)	no	IN Single-Coil (bridge-PU)	
8. Position C (bridge)	no	OUT Hummbucker (bridge-PU)	

- Pick up height adjustment (two screws on the back of the guitar)

Changing strings:

Ideally use light gauge strings: ,010 / ,013 / ,017 / ,026 / ,036 / ,046

1) Removing old string(s)

- When replacing string(s), preferably clip old strings in half, before removing them from guitar. In doing so the old crimped string ends can be removed more easily right at the Nut/Stringholder.

2) Restringing the guitar:

- Before inserting new string, turn Tuningknobs counterclockwise until they come to a halt (do not use excessive force!).
- Feed new string through opening in the back of the Guitar and out the top (saddle).
- Pull the string all the way through the top hole until it resists your tug.
- Feed the string through the appropriate hole in the String-holder-plate at the nut and wrap the string clockwise, ¾ turn around the String-fastening-screw. String should rest between Screw head and washer.
- While holding string in slight tension, tighten screw (use wrench integrated on the TheBone® back side). Do not use excessive force! (It dose not use much force for the string to be clamped tight).
- Proceed in tuning string by turning Tuningknobs clockwise.
- Excess string length at String-fastening-screw can be removed by bending string back and forth until it brakes.

Note: The tensioning distance is limited and will come to a halt. This might happen if the string is to loosely restrung. "never use force!"

The "BodyClip"

When folding open the "BodyClip" the last move is to fit *endpin* in to *endpin-hole*

When collapsing the "BodyClip": First unlock *endpin* from *endpin-hole*. When detaching the *interlocking fittings* (pulling apart and fold) be sure to position your grip (hands) close to where the *fitting* comes apart. When collapsing the back segment (the one with the strap holder), be sure to first disconnect the side, with the radius (rubber cover).

When attaching the "Body-Clip" screws to the instrument, be sure that the "Body-Clip" segments lie flat (in one plane). Also make sure that screws are screwed to the body in a right angle without using any force.

Fitting "the BONE" in to the bag:

TheBone® fits best with strings facing the outside of bag. In doing so, the folded Bodyclip fits nicely alongside the rounded part of the guitar neck, in the space opposite the protective divider inside the bag.

The Bag strap can also be used as guitars strap

Adjusting string height and scale:

please have this done by a guitar professional.

We wish you grate pleasure with your new TheBone-guitar®
TRIFF Guitars of Switzerland
(Jan. 2006)